

NON-TITLE V TECHNICAL SUPPORT DOCUMENT

PERMIT NUMBER: 040136

BUSINESS NAME: Hickman's Egg Ranch

SOURCE TYPE: Poultry Egg Production

PERMIT ENGINEER: Sara Seuberling

App. ID(s): 408551

Revision(s): 2.0.2.0

Revision Type(s): Minor Modification

Date Prepared: 08/20/2015

BACT: No MACT: Yes NSPS: Yes SYNTH MINOR: No AIRS: No

DUST PLAN REQUIRED:NoDUST PLAN RECEIVED:NoO&M PLAN REQUIRED:NoO&M PLAN RECEIVED:No

PORTABLE SOURCE: No SITE VISIT: 08/19/2015

PROCESS DESCRIPTION:

This facility houses chickens for the production of eggs for human consumption. Each barn is equipped with an emergency generator to power fans during an electrical outage. These generators emit products of combustion while in operation, such as carbon monoxide (CO), nitrogen oxides (NOx), particulate matter (PM), volatile organic compounds (VOC), and sulfur oxides (SOx) . A propane-fuled manure dryer also creates products of combustion. A crematory is located on-site for the disposal of chicken carcasses but is not currently connected to a fuel source. Non-resale gasoline is stored and dispensed on-site, which emits VOC.

PM is produced from an on-site feed mill, manure drying, composting, feed delivery, unpaved roads, and unpaved parking lots. However, Eric Massey, director of the Air Quality Division at the Arizona Department of Environmental Quality (ADEQ), agreed that all of these operations are considered agricultural practices and are therefore subject to Best Management Practices (BMPs) under A.R.S. 49- 457 rather than County Rules 310 and 311. BMPs are regulated by ADEQ rather than Maricopa County, so conditions regarding those operations are excluded from the permit.

PERMIT HISTORY:

Date	Revision	
Received	Number	Description
10/15/2004	0.0.0.0	Submitted application for new permit to operate a crematory and emergency generators at the egg farm.
03/09/2011	0.0.1.0	Minor modification requested to add emergency generators and gasoline storage to the equipment list.
03/10/2011	1.0.0.0	Submitted permit renewal application.
10/11/2011	0.0.2.0	Minor modification requested to add a feed mill to the facility
12/07/2011	1.0.1.0	Minor modification requested to install a grain receiving and storage operation at the facility.
05/20/2013	1.0.2.0	Minor modification requested to add three emergency generators to the equipment list.
06/24/14	2.0.0.0	Submitted permit renewal application.
06/24/14	2.0.1.0	Minor modification requested to add three emergency generators to the equipment list.
07/20/2015	2.0.2.0	Minor modification requested to add a 15 MMBtu/hr propane-fueled rotary dryer for manure processing along with a 15,000 propane tank. The Permittee also requested the equipment list to be updated with a replacement emergency generator. Requirements for the feed mill were removed since they are regulated under BMPs enforced by ADEQ.

PURPOSE FOR APPLICATION:

Minor modification to install a rotary dryer with baghouse to process chicken manure, remove requirements for feed operations, and replace a 1998 model year generator with a 2015 model year generator.

A. APPLICABLE COUNTY REGULATIONS:

Rule 100: General Provisions and Definitions

Rule 200: Permit Requirements

Rule 220: Non-Title V Permit Provisions

Rule 280: Fees: Table C (Emergency generators and non-resale gasoline storage)

Rule 314: Open Outdoor Fires

Rule 320: Odors & Gaseous Air Pollutants

Rule 324: Stationary Internal Combustion Engines

Rule 353: Gasoline in Stationary Dispensing Tanks

Per Rule 353 §305.2, the gasoline storage tank is exempt from all requirements of Rule 353 except for cap, spills and liquid leakage provisions in §301 of that rule since the gasoline stored at the facilty is used for normal farm operations.

Note: The 15 MMBtu/hr dryer is not subject to Rule 323 since it does not fit any of the applicable equipment types listed in Rule 323 §102.

Note: Rules 310 and 311 do not apply to this facility since the Permittee is following BMPs regulated by ADEQ. Under A.R.S. 49-457, agricultural activities, including poultry farms, are subject to BMPs for the control of particulate emissions.

B. APPLICABLE FEDERAL REGULATIONS:

40 CFR 60 Subpart IIII (Standards of Performance for Stationary Compression Ignition ICE) applies to each diesel-fueled generator manufactured after 4/1/06.

40 CFR 63 Subpart ZZZZ (NESHAP for Stationary RICE) applies to each engine not subject to 40 CFR 60 Subpart IIII.

40 CFR 63 Subpart CCCCC (NESHAP for Gasoline Dispensing Facilities) applies to the gasoline storage tank. Since the gasoline throughput is less than 10,000 gallons per month, only gasoline handling requirements from 40 CFR §63.11115 and 63.11116 apply. Requirements for a submerged fill pipe and a vapor balance system are reserved for larger facilities.

Non-Applicable Federal Regulations

40 CFR 60 Subart DD (Standards of Performance for Grain Elevators) does not apply to the facility since the grain storage and processing operations do not meet the definition of grain terminal elevator or grain storage elevator provided in 40 CFR 60.301. Grain terminal elevators do not include those located at livestock feedlots. None of the feed is meant for human consumption so dry corn milling does not meet the definition of grain storage elevator.

40 CFR 63 Subpart DDDDDDD (NESHAP for Area Sources: Prepared Feeds Manufacturing): This facilities is primarily engaged in raising/feeding chickens so it is not classified as a prepared feed manufacturing facility, per 40 CFR 63.11627. If this facility was considered a prepared feed manufacturing facility, it would most likely be subject to this Subpart since a material used in the feed contains manganese in excess of 1.0% by weight.

C. AIR POLLUTION CONTROL EQUIPMENT/EMISSION CONTROL SYSTEM(s):

System description	Quantity	Comments:
Rotory Dryer Baghouse	1	Controls particulate emissions from the rotary dryer. It is regulated by
		ADEQ under agricultural BMPs rather than the Control Officer.
Corn Grinder	1	The grinder is self-contained to reduce particulate emissions. It is
		regulated by ADEQ under agricultural BMPs rather than the Control
		Officer.

Feed Mixer	1	The mixer is self-contained to reduce particulate emissions. It is
		regulated by ADEQ under agricultural BMPs rather than the Control
		Officer.

D. EMISSIONS:

FACILITY WIDE ALLOWABLE EMISSIONS

Pollutants	Engines	Dryer	Gasoline Storage	Facility wide Daily Emissions*	Facility wide Annual Emissions
CO:	22,653 lbs/yr	2,558 lbs/yr		10 lbs	25,212 lbs
NOx:	45,435 lbs/yr	4,435 lbs/yr		17 lbs	49,869 lbs
PM2.5:	2,767 lbs/yr	239 lbs/yr		1 1b	3,005 lbs
PM10:	2,767 lbs/yr	239 lbs/yr		1 lb	3,005 lbs
VOC:	6,146 lbs/yr	273 lbs/yr	4,800 lbs/yr	15 lbs	11,219 lbs
SOX:	463 lbs/yr	7 lbs/yr		1 lb	470 lbs

^{*}Daily emissions exclude emissions from the emergency engines.

E. HAP EMISSION IMPACTS:

Based on the information provided in the permit application, the facility emits insignificant amount of HAPs therefore, SCREEN modeling was not performed per the Department's HAPs policy.

F. PERFORMANCE TESTING:

Testing is not required for this facility at this time.

G. REGULATORY REQUIREMENTS AND MONITORING:

Condition 1 states that the Permittee must submit a permit revision before reconnecting the crematory to a fuel source. The facility was previously permitted for a crematory but it is no longer used.

Condition 2 was included since the facility was issued an NOV for a mulch fire 03/07/14.

Conditions 3-5 were taken from Rule 320 and were included due to the potential for odors from manure handling and composting operations.

Conditions 6-15 are based on the most current template for emergency engines subject to Rule 324, NSPS IIII and 40 CFR 63 Subpart ZZZZ. The operating limit was set at 355 hours per year to keep the facility from exceeding the BACT threshold for annual NOx emissions of 25 tons/yr.

Conditions 16-20 regulate the non-retail gasoline storage tank, which is subject to Rule 353 §301 and 40 CFR 63 Subpart CCCCC. Condition 17 contains throughput limits and a restriction to only fuel farm implements to keep the facility from becoming subject to submerged fill pipe and vapor balance requirements.

Conditions 21-22 regulate the manure dryer and were included to keep the facility from exceeding any applicable threshold, such as BACT.

APPENDIX



040136 Emission Worksheet

Propane-Fueled Equipment Emissions

Emissions from the rotary dryer are calculated below using EPA emission factors from AP-42. The application included both operating times and fuel usage so emissions were calculated separately based on operating time and fuel usage for comparison purposes.

Input rating of	equipment			
1)	15.0 MM Btu/hr	AND		
2)	0.0	THE CONTRACTOR OF THE CONTRACT		
3)	0.0		294000000000000000000000000000000000000	
Total	15.0 MM Btu/hr			
		HALVOOR TO ANNUAL TO ANNUA		

mission facto	ors (AP-4	2 Table 1.5-1)	<u>Constants</u>		
CO:	7.5	lb/1000 gal	91,500	btu/gal	(AP-42 Section 1.5-1
NOx:	13	lb/1000 gal	8	hr/day	
PM10:	0.7	lb/1000 gal	260	day/yr 🦽	
PM2.5:	0.7	lb/1000 gal	Approximately stated in the state of the sta	74	
VOC:	0.8	lb/1000 gal			
SOx	0.02	lb/1000 gal (Emis	sions Inventory)	

		_	
Emicoiono	Docod on	Onorotina	Haurer
Emissions	Daseu on	Operanno	nouis.

CO:	9.8	lbs/day	2,558	lbs/yr
NOx:	17.0	lbs/day	4,433	lbs/yr
PM10:	0.9	lbs/day	239	lbs/yr
PM2.5:	0.9	lbs/day	239	lbs/yr
VOC:	1.0	lbs/day	273	lbs/yr
SOx	0,0	lbs/day	7	lbs/yr

Propane usage limit (from	application): 3	41,120 gals/yr

Emissions Based on Fuel Usage:

CO:	2558	ibs/yr	
NOx:	4435	lbs/yr	
PM10:	239	lbs/yr	
PM2.5:	239	lbs/yr	
VOC:	273	lbs/yr	
SOx	7	lbs/yr	

Emission Worksheet for New Diesel Engines

355 annual hours of operation

1 KW= 1.341 HP

40 CFR 89 Non-Road Diesel Engine Standards

		Em	ission Fact	ors (g/kw-l	hr)
Rated Power	Emission Standard	СО	NMHC+ NOx	PM	НС
130≤kW<560	Tier 3	3.5	4	0.2	1.3
kW>560	Tier 2	3.5	6.4	0.2	1.3

Cummins QSL9-G7 NR3 Manufacturer's Specifications

NOx:	1306 g/hr
VOC:	32 g/hr

Emissions

Except as noted, CO, NOx and PM10 emission factors are set at the appropriate emission standards for non-road diesel engines specified in 40 CFR 89.112. VOC emissions are set at the Tier 1 limit since Tier 3 standards consist of NOx plus non-methane hydrocarbons rather than VOC alone. The SOx factor was taken from AP-42 Table 3.4-1 and is based on the sulfur content of diesel fuel burned in the engines.

	Emission Factors	Factor Source
SOx:	0.0001 lbs/hp-hr	AP-42

	Power	Engine	Emission	Emissions (lbs/yr)				
I.D. #	(HP)	Year	Standard	со	NOx:	PM10	VOC:	SOx:
G-1	755	2010	Tier 2	1,542	2,820	88	573	33
G-10	310	2007	Tier 3	633	724	36	235	13
G-11	352	2007	Tier 3	719	822	41	267	15
G-12	685	2008	Tier 3	1,399	1,599	80	520	30
G-13	422	2008	Tier 3	862	985	49	320	18
G-14	422	2008	Tier 3	862	985	49	320	18
G-15	237	2008	Tier 3	484	553	28	180	10
G-16	422	2008	Tier 3	862	985	49	320	18
G-17	422	2010	Tier 3	862	985	49	320	18
G-18	422	2010	Tier 3	862	985	49	320	18
G-19	422	2010	Tier 3	862	985	49	320	18
G-20*	464	2012	Tier 3	948	1,022	54	25	20
G-21*	464	2012	Tier 3	948	1,022	54	25	20
G-22*	464	2012	Tier 3	948	1,022	54	25	20
G-23*	464	2012	Tier 3	948	1,022	54	25	20
G-24*	464	2012	Tier 3	948	1,022	54	25	20
G-25*	464	2012	Tier 3	948	1,022	54	25	20
G-39*	464	2015	Tier 3	948	1,022	54	25	20
FM1	324	2010	Tier 3	662	756	38	246	14
Total:	8443			17,246	20,343	986	4,114	364
*Emission rates for NOx and VOC are based on the engine manufacturer's specification sheet.								

Emission Worksheet for Old Diesel Engines

	Power		
I.D. #	(HP)		
G-2	380		
G-4	380		
G-5	380		
G-6	380		
G-7	380		
G-9	380		
TOTAL	2,280		

355 annual hours of operation

0.015% S, allowable sulfur content in fuel SOx = 0.00809(S) AP-42 Table 3.4-1

Emission factors (AP-42 Table 3.3-1)

CO: 0.0067 lbs/hp-hr
NOx: 0.0310 lbs/hp-hr
PM10: 0.0022 lbs/hp-hr
PM: 0.0022 lbs/hp-hr
VOC: 0.0025 lbs/hp-hr
SOx: 0.0001 lbs/hp-hr

Combustion Emissions

	Old Generators	New Generators	Propane Dryer	Total Emissions	
CO:	5,407 lbs/yr	17,246 lbs/yr	2,558 lbs/yr	25,212 lbs/yr	
NOx:	25,092 lbs/yr	20,343 lbs/yr	4,435 lbs/yr	49,869 lbs/yr	
PM10:	1,781 lbs/yr	986 lbs/yr	239 lbs/yr	3,005 lbs/yr	
PM2.5:	1,781 lbs/yr	986 lbs/yr	239 lbs/yr	3,005 lbs/yr	
voc:	2,032 lbs/yr	4,114 lbs/yr	273 lbs/yr	6,419 lbs/yr	
SOX:	99 lbs/yr	364 lbs/yr	7 lbs/yr	470 lbs/yr	

Gasoline S	Storage Tanks	Worksheet:		
72				
<u>Maximum t</u>	hroughput		<i>(</i> 77)	
		\#\#\		
120,000	gallons/year			
10,000	gallons/month	A V		
Total Andreas				
Abovegrou	nd Tank VOC E	mission Rate:	40	lbs/1000 gal.
(Emissions	Inventory Instr	uction Sheet)		
VOC Emis	sions			
Daily:	14	lbs VOC/day	Based on 3	30 days per month.
Monthly:	400	lbs VOC/mo.		
Yearly:	4,800	lbs VOC/year		



NON-TITLE V COMPLETENESS DETERMINATION CHECKLIST

Items 1-15 Front page: Items 1 to 15 (14 for Renewals) must be completed.

Notes to engineer:

- For renewal applications the source must either answer 'No' to questions 2-5 or submit an application for a permit modification.
- aligants do not know the SIC ands on NAICS ands for their industr

Permit Engineer:	Sara Seuberling		_ Date:	7/29/2014	
Completeness revie Application determin	-		Complete: x	Incomple	te:
Permit number:	040136				
Business name:	Hickman's Egg Ranch				
	s are for very common materi	-		p. 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
	al safety data sheet (MSDS) i		_	-	the
	npleting Sections A, B, C, D, lication are included at the be				2, Y and
~	g Section Z: Many applicants nit application with a blank S		n these engineerin	g calculations	i. We
	ant needs to complete only the	ose sections of the permit Complete			J/A:
approved by the dus		Complete	-	<u> </u>	J/A: x
	trol plan, if required, must ac	company the permit appli	cation. The plan v	will be revie	wed and
	plan is required only for a corthe O&M plan with the appli		submit it after rece	iving the pern	booth. nit. J/A: x
needed for some small	-	Complete			J/A: x
Item 17: A simple n	rocess flow diagram on a star	Complete			VA: x v not be
construction drawing	<u> </u>				·
Item 16: A simple	site diagram has been includ	ed nreferably on a stand	· · · · · · · · · · · · · · · · · · ·	Detailed bluer	
• Items 5, 7 c	and 14: These may be the sam	e for many applicants.	Complete: x	Incomple	ite:
application the cod	ny applicants do not know the le can be obtained by doing ar	n on-line search. http://ww		War and the second seco	ıtml